



CITY OF ALBANY
Public Works Department
ADDENDUM #1

SS-22-01, Cox Creek Interceptor Improvements: Phase 2

In order to clarify the intent of the Specifications and Drawings, the following provisions are provided and shall be considered part of the contract documents.

In order to ensure that all bidders are aware of these provisions, each bidder must sign this addendum below and attach it to the proposal.

IMPORTANT: Failure to include a signed Addendum could result in the disqualification of your bid.

SCHEDULE OF CONTRACT PRICES

Replace the existing Schedule of Contract Prices with the new attached Schedule of Contract Prices. The new schedule includes the following changes:

- Item No. 35: 60-Inch Precast Manhole with Outside Drop: Decrease the quantity from 2 each to 1 each.
- Item No. 36: Abandon Existing Manhole: Decrease the quantity from 9 each to 7 each.
- Item No. 39: Connect 15-Inch Sewer: New bid item
- Item No. 40: 60-Inch Precast Manhole with Inside Drop: New bid item

I-9. TEMPORARY TRAFFIC CONTROL

Add the following new text:

Sidewalks and pathways may be closed within the project limits during construction. The traffic control plan must include temporary closures or detours of sidewalk and pathways.

SECTION III: TECHNICAL SPECIFICATIONS – BID ITEMS

Item No. 3 – Erosion Prevention and Sediment Control:

Add the following text:

Compost socks must be photodegradable or biodegradable. After project completion, compost socks shall slit open, raked out, seeded, and left in place.

Item No. 8 – Remove and Replace 8-Inch PCC Sidewalk

Add the following text:

A felt expansion joint must be installed along the face of retaining walls.

Item No. 26 – 36-Inch Casing and Bore w/24-Inch PVC Carrier Pipe:

Replace the second paragraph with the following new text updating the thickness of the casing pipe and placement of pipe insulators (new text shown in bold):

The casing must be 36-inch diameter ASTM A53, Type E, with minimum wall thickness of 0.3125 inches. Calpico Model M-8-SS pipe insulators with standard type skids must be installed, three per stick of pipe, with one insulator in the middle of each stick of pipe and one insulator installed within two feet of each end. Each end of the steel casing must be plugged with a minimum six inches of grout to prevent the movement of material into the casing. No material shall be placed in the annular space between the casing and carrier pipes.

Item No. 27 – 48-Inch Casing and Bore w/30-Inch PVC Carrier Pipe:

Replace the second paragraph with the following new text updating the diameter of the casing pipe and placement of pipe insulators (new text shown in bold):

The casing must be 48-inch diameter ASTM A53, Type E, with minimum wall thickness of 0.625 inches. Calpico Model M-8-SS pipe insulators with standard type skids must be installed, three per stick of pipe, with one insulator in the middle of each stick of pipe and one insulator installed within two feet of each end. Each end of the steel casing must be plugged with a minimum six inches of grout to prevent the movement of material into the casing. No material shall be placed in the annular space between the casing and carrier pipes.

Add the following new bid items:

Item No. 39 – Connect 15-Inch Sewer:

See *Standard Construction Specifications* Sections, 401 and the Construction Drawings.

This item provides for connecting an existing 15-inch concrete sewer main to a new manhole as shown on the Construction Drawings.

Payment for this bid item will be on a lump-sum basis and will include all equipment, labor, materials, and incidentals required to complete the work.

Item No. 40 – Construct 60-Inch Precast Manhole with Inside Drop:

See *Standard Construction Specifications* Sections, 402 and 403 and the Construction Drawings.

This bid item includes construction of a new 60-inch diameter precast manhole with an 8-inch inside drop per the *Standard Construction Specifications*, applicable Standard Details, and the Construction Drawings. Pipe connections to the manhole are incidental to this bid item. Inside drop connections shall be considered incidental to this bid item.

Interior joints between new precast manhole components must be sealed with approved non-shrink grout. The bench must be constructed with a 1:12 slope to the springline of the pipe.

Payment for this bid item will be on a per-each basis and will include all equipment, labor, materials, and incidentals required to complete the work.

CONSTRUCTION DRAWINGS

Sheet No. 6: The sewer stub at SSMH-12 is 24-inch PVC, not 30-inch PVC as labeled

Contractor's Signature

Date

Company Name *(please type or print)*

SCHEDULE OF CONTRACT PRICES

ITEM NO.	BID ITEMS	APPROX. QUANTITY	UNIT OF MEASURE	UNIT PRICE DOLLARS/CTS	TOTAL AMT. DOLLARS/CTS
1	Mobilization	1	Lump Sum		
2	Temporary Traffic Control	1	Lump Sum		
3	Erosion Prevention and Sediment Control	1	Lump Sum		
4	Trench Dewatering	1	Lump Sum		
5	Sewer Bypass Pumping	1	Lump Sum		
6	Tree and Shrub Removal	1	Lump Sum		
7	Remove and Replace Standard Curb and Gutter	20	Linear Foot		
8	Remove and Replace 8-Inch PCC Sidewalk	950	Square Yard		
9	Remove and Replace 4-Inch PCC Sidewalk	55	Square Yard		
10	Truncated Domes	20	Square Foot		
11	Remove and Reinstall Decorative Light Pole	2	Each		
12	Remove and Reinstall Electrical Cabinet	1	Lump Sum		
13	Remove and Replace Bollard	2	Each		
14	Private Landscape Restoration	1	Lump Sum		
15	Hydroseeding	1	Lump Sum		
16	Install New Street Sign	1	Each		
17	2-Inch Asphalt Trench Patch	230	Square Yard		
18	4-Inch Asphalt Trench Patch	65	Square Yard		
19	Reconnect 4-Inch PVC Storm Lateral	30	Linear Foot		
20	Reconnect 12-Inch RCP Storm Drain	20	Linear Foot		
21	8-Inch PVC Sewer Main	10	Linear Foot		
22	10-Inch PVC Sewer Main	80	Linear Foot		
23	18-Inch PVC Sewer Main	70	Linear Foot		
24	24-Inch PVC Sewer Main	215	Linear Foot		
25	30-Inch PVC Sewer Main	955	Linear Foot		

ITEM NO.	BID ITEMS	APPROX. QUANTITY	UNIT OF MEASURE	UNIT PRICE DOLLARS/CTS	TOTAL AMT. DOLLARS/CTS
26	36-Inch Casing and Bore w/24-Inch PVC Carrier Pipe	75	Linear Foot		
27	48-Inch Casing and Bore w/30-Inch PVC Carrier Pipe	111	Linear Foot		
28	4-Inch Sewer Service Connection to 24-Inch Main	1	Each		
29	6-Inch Sewer Service Connection to 30-Inch Main	2	Each		
30	4-Inch Private Sewer Service	1	Each		
31	Connect to Existing Manhole	1	Each		
32	Standard Precast Manhole	2	Each		
33	Standard Precast Manhole with Outside Drop	1	Each		
34	60-Inch Precast Manhole	5	Each		
35	60-Inch Precast Manhole with Outside Drop	1	Each		
36	Abandon Existing Sewer Manhole	7	Each		
37	Abandon Sewer Main	1	Lump Sum		
38	8-Inch Ductile Iron Water Line	25	Linear Foot		
39	Connect 15-Inch Sewer	1	Lump Sum		
40	60-Inch Precast Manhole with Inside Drop	1	Each		
SUM OF EXTENDED TOTALS					

NOTE: Subject to change if addition or extensions are in error.

Bidder's Signature	Company Name <i>(please print)</i>	Date
Bidder's Name <i>(please print)</i>	Mailing Address <i>(please print)</i>	CCB License Number
Bidder's Title <i>(please print)</i>	City, State Zip	Federal Tax ID Number
Telephone No.: _____	Fax No.: _____	Email: _____